Three Points



Mobile Scissor Lift Platform

Hydraulic • Stationary • Mobile • Self-Propelled • Tracked • Docking • Loading • Customizable

www.threepointslift.com

Three Points

Mobile Scissor Lift Platform













www.threepointslift.com

Three Points

Mobile Scissor Lift Platform

			
base bracket	Optional： Self-propelled	Foldable basket	Inflatable tires
			
Ladder to enter the basket	Distribution box	Manual traction and steering lever	spirit level

www.threepointslift.com

Three Points

Mobile Scissor Lift Platform

			
remote control	hydraulic oil tank hydraulic pump	Hydraulic cylinder	Hand crank outrigger
			
steering structure	AC plug	Fall prevention chain	Electricity meter

www.threepointslift.com

Three Points

Model selection

Options:

※DC motor, AC/DC hybrid, diesel engine, diesel + battery;
※Self-propelled or trailer-towed;
※Extendable/custom platform;
※Explosion-proof motor, solid tires, hydraulic legs;
※pull-out supports,overload/tilt alarms, remote control, buzzer

Model	Platform size	Load-kg	Working height-m	Overall dimensions-mm	weight-kg
TP-ML0.5-6	1800*820	500	6	1980*960*1200	700
TP-ML0.5-8	1800*820	500	8	1980*960*1280	750
TP-ML0.5-10	1800*820	500	10	1980*960*1390	900
TP-ML0.5-11	1800*820	500	11	1980*960*1390	950
TP-ML0.5-12	2100*1200	500	12	2280*1350*1550	1260
TP-ML0.3-13	2100*1200	300	13	2280*1340*1700	1400
TP-ML0.5-15	2550*1500	500	15	2750*1670*1840	2160
TP-ML0.5-16	2830*1500	500	16	3000*1730*1870	2500
TP-ML0.5-18	2830*1500	500	18	3000*1730*2070	3000
TP-ML0.5-20	3165*1600	500	20	3350*1800*2430	4000
TP-ML0.5-22	3500*1800	500	22	3700*2200*3100	6000
TP-ML0.5-24	3800*2000	500	24	4000*2300*3100	8000
TP-ML0.5-26	4120*2000	500	26	4300*2300*3100	11000
TP-ML1.0-6	2100*1200	1000	6	2280*1350*1240	1100
TP-ML1.0-8	2100*1200	1000	8	2280*1350*1360	1400
TP-ML1.0-10	2100*1200	1000	10	2280*1350*1480	1585
TP-ML1.0-12	2100*1200	1000	12	2280*1350*1600	1650
TP-ML1.0-14	2550*1500	1000	14	2750*1670*1800	2860
TP-ML1.0-16	2830*1500	1000	16	3000*1750*1850	3100
TP-ML1.0-18	3150*1600	1000	18	3400*1910*2350	4500
TP-ML1.0-20	3150*1600	1000	20	3400*1910*2550	4800
TP-ML2.0-8	2150*1300	2000	8	2350*1450*1530	1750
TP-ML2.0-10	2150*1300	2000	10	2350*1450*1690	2050
TP-ML2.0-12	2150*1300	2000	12	2350*1450*1850	2400
TP-ML2.0-14	2650*1600	2000	14	2850*1730*2420	3200
TP-ML2.0-16	2900*1600	2000	16	3100*1730*2420	5400
TP-ML2.0-18	3200*1800	2000	18	3400*2200*3100	5800
TP-ML3.0-14	2900*1800	3000	20	3100*2200*3000	6000
TP-ML3.0-12	2400*1500	3000	12	2500*1800*2400	4000

www.threepointslift.com

Three Points

Self-Propelled Scissor Lift

Flexible, Efficient, and Operator-Friendly










www.threepointslift.com

Three Points

Self-Propelled Scissor Lift

Flexible, Efficient, and Operator-Friendly

			
Smart Control Panel	Emergency Stop Button	Movable Joystick Handle	Forklift Pockets for Easy Transport
			
Charging Port	Heavy-Duty Battery Pack	Horn & Cooling Fan	Power Cut-Off Switch

www.threepointslift.com

Three Points

Self-Propelled Scissor Lift

Flexible, Efficient, and Operator-Friendly

			
Silent Non-Marking Tires	*Reinforced Climbing Ladder*	*Hydraulic Tank & Pump*	*Extendable Platform Deck*
			
Foldable Platform Rails	*Foot Pedal for Deck Extension*	*Optional: Auto-Leveling Hydraulic Outriggers*	*High-Pressure Hydraulic Hoses*

www.threepointslift.com

Three Points

Model selection

Model	Platform size -mm	Load-kg	Working height-m	Overall dimensions-mm	weight-kg
TP-SL-0.32-8	2300*1170	320Kg	8	2500*1200*1775	2200kg
TP-SL-0.32-10	2300*1170	320Kg	10	2500*1200*1810	2400kg
TP-SL-0.32-12	2300*1170	320Kg	12	2500*1200*2025	2600kg
TP-SL-0.32-14	2300*1170	320Kg	14	2500*1200*2150	2800kg
TP-SL-0.32-16	2650*1280	320Kg	16	2800*1280*2150	3400kg
TP-SL-0.32-18	3000*1280	320Kg	18	3200*1600*2440	4338KG
TP-SL-Mini-0.3-8	1750*760	300Kg	8	1900*780*1920	1350Kg
TP-SL-Mini-0.3-6 electric wheel	1290*760	300Kg	6	1440*780*1890	1100Kg
TP-SL-0.32-8 Narrow style	2300*900	320Kg	8	2500*930*1810	2150kg
TP-SL-0.32-10 Narrow style	2300*900	320Kg	10	2500*930*2250	2250kg

Standard configuration :

- Proportional Control
- Tilt Alarm
- Motion Alarm Buzzer
- Silent Non-marking Tires
- Emergency Stop Button
- Charging Protection
- Flashing Warning Light
- Maintenance Support

www.threepointslift.com

Three Points

Tracked Self-Propelled Scissor Lift

Built for Tough Terrain & Heavy-Duty Applications













※*All-Terrain Mobility*
Rubber tracks provide superior grip and balance on mud, gravel, and slopes.

※*Self-Propelled System*
Easy maneuvering without external towing or pushing.

※*Stable & Safe Lifting*
Equipped with auto-leveling outriggers and tilt alarm for safety.

※*Dual Power Options*
Available in diesel + battery hybrid version for flexibility on job sites.

※*Heavy Load Capacity*
Built to carry tools and personnel up to 320kg with ease.

www.threepointslift.com

Three Points

Model selection

Model	Platform size -mm	Load-kg	Working height-m	Overall dimensions-mm	weight-kg
TP-SL- 0.32-6 steel track	2300*1170	320K g	6	2560*1600*1450	2400kg
TP-SL- 0.32-8 steel track	2300*1170	320K g	8	2560*1600*1500	2500kg
TP-SL- 0.32-10 steel track	2300*1170	320K g	10	2560*1600*1560	2700kg
TP-SL- 0.32-12 steel track	2300*1170	320K g	12	2560*1600*1700	3000kg
TP-SL- 0.32-14 steel track	2300*1170	320K g	14	2900*1900*1940	3200kg
TP-SL- 0.32-16 steel track	2650*1280	320K g	16	3000*2000*2040	3600kg

Standard :
- *Auto-Leveling Hydraulic Outriggers;*
- *Steel Tracks*

Optional :
- *Manual Outriggers;*
- *200Ah Lithium Battery;*
- *Rubber Tracks;*
- *Auto-Leveling Removal*

www.threepointslift.com